

GROUND - UP RANGE

OUTDOOR

GROUND DIRECT

GROUND - UP RANGE



bridgelux®

CREE

OSRAM

SAMSUNG



PRODUCT OVERVIEW

Code	GUP
Product Name	Ground UP Range
Power	10W
Input Voltage	DC 24V
Total Lumen Efficiency	800 lum
LED CHIP BRAND	Bridgelux/samsung/Cree/Osram
CRI	Ra≥90 /
CCT	3000K / 4000K / 6000K/ RGBW
Beam Angle	15°, 20°, 40°, 60°
Lamp Cup	Stainless steel / Black
IP Rating	IP67
Driver Type	SWARVEN
Material	Stainless Steel
Dimension	φ150x142mm
Manufacturer's Warranty	5 years
Installation method	Inground Uplight

Swarven web : <https://swarven.com/>

Lumen efficiency can be increased upon request and based on the required quantity.

For coding pearpose ,

1-CCT :- For 2700K add W to code, For 3000k add L to code, For 4000K add D to code, for 6500K add S to code & For Tunable(2700K-6500K) add Z to code

2- Voltage : Put the number of the voltage (7 or 12)

3- Beam angle : Put the number of the Angle (24* or 38*)

4- Put I with No. that need IP (20*40*&44*) (Ex : CR- Code , 7- W ,2700K - K, 24*- Beam Angle , IP20 - IP rating , D - Dali)

5- Driver : (Triac, Leading Edg, 0-10v,1-10v,zigbee & dally on required) (On / Off)ST , Trick (T) , (0 - 10 v) V , (1 - 10 v) V1 & Dali (D)

Emergency add EM to code (EM - Emergency)