

**MAGNETIC FOLD GRILL
LIGHT
MAGNETIC RANGE**

INDOOR

MAGNETIC FOLD GRILL LIGHT



bridgelux®

CREE ⇄

OSRAM

SAMSUNG



PRODUCT OVERVIEW

Item Code	680101441010	680101441027	680101441034
Code	MG-S	MG-M	MG-L
Product Name	Magnic Range	Magnic Range	Magnic Range
Power	6 W	12 W	18 W
Input Voltage	85-240V	85-240V	85-240V
Total Lumen Efficiency	500 lum	1050 lum	1620 lum
LED CHIP BRAND	Bridgelux/samsung/Cree/Osram	Bridgelux/samsung/Cree/Osram	Bridgelux/samsung/Cree/Osram
CRI	Ra≥90 / Ra≥95 (On request)	Ra≥90 / Ra≥95 (On request)	Ra≥90 / Ra≥95 (On request)
CCT	2700K/3000K/4000K/6500K	2700K/3000K/4000K/6500K	2700K/3000K/4000K/6500K
Beam Angle	24°/36°	24°/36°	24°/36°
Lamp Cup	Brilliant Black	Brilliant Black	Brilliant Black
IP Rating	IP20 / IP 40	IP20 / IP 40	IP20 / IP 40
PF	PF ≥ 0.9	PF ≥ 0.9	PF ≥ 0.9
Driver Type	LIFUD/EAGLERISE/SWARVEN	LIFUD/EAGLERISE/SWARVEN	LIFUD/EAGLERISE/SWARVEN
Material	Aluminum / Heat Sink	Aluminum / Heat Sink	Aluminum / Heat Sink
Dimension	L 112*W22*H110	L 220*W22*H110	L 330*W22*H120m
Manufacturer's Warranty	5 years	5 years	5 years
Installation method	Inside Magnetic Track	Inside Magnetic Track	Inside Magnetic Track

Swarven web : <https://swarven.com/>

Lumen efficiency can be increased upon request and based on the required quantity.

For coding pearpose ,

1-CCT :- For 2700K add W to code, For 3000K add L to code, For 4000K add D to code, for 6500K add S to code & For Tunable(2700K-6500K) add Z to code

2- Voltage : Put the number of the voltage (7 or 12)

3- Beam angle : Put the number of the Angle (24° or 38°)

4- Put I with No. that need IP (20°40°&44°) (Ex : CR- Code , 7- W ,2700K - K, 24°- Beam Angle , IP20 - IP rating , D - Dali)

5- Driver : (Triac, Leading Edg, 0-10v,1-10v,zigbee & dally on required) (On / Off)ST , Trick (T) , (0 - 10 v) V , (1 - 10 v) V1 & Dali (D)

Emergency add EM to code (EM - Emergency)