


MAGNETIC DIFFUSE LIGHT

SLIM MAGNETIC RANGE

INDOOR

MAGNETIC DIFFUSE LIGHT



bridgelux®

CREE

OSRAM

SAMSUNG



PRODUCT OVERVIEW

Item Code	680101441416
Code	MG-SD1
Product Name	Slim Magnic Range
Power	10 W
Input Voltage	85-240V
Total Lumen Efficiency	900 lum
LED CHIP BRAND	Bridgelux/samsung/Cree/Osram
CRI	Ra≥90 / Ra≥95 (On request)
CCT	2700K/3000K/4000K/6500K
Beam Angle	120*
Lamp Cup	Brilliant Black
IP Rating	IP20 / IP 40
PF	PF ≥ 0.9
Driver Type	LIFUD/EAGLERISE/SWARVEN
Material	Aluminum
Dimention	230x26x24mm
Manufacturer's Warranty	5 years
Installation method	Inside Magnetic Track

Swarven web : <https://swarven.com/>

Lumen efficiency can be increased upon request and based on the required quantity.

For coding pearpose ,

1-CCT :- For 2700K add W to code, For 3000k add L to code, For 4000K add D to code, for 6500K add S to code & For Tunable(2700K-6500K) add Z to code

2- Voltage : Put the number of the voltage (7 or 12)

3- Beam angle : Put the number of the Angle (24* or 38*)

4- Put I with No. that need IP (20*40*&44*) (Ex : CR- Code , 7- W ,2700K - K, 24*- Beam Angle , IP20 - IP rating , D - Dali)

5- Driver : (Triac, Leading Edg, 0-10v,1-10v,zigbee & dally on required) (On / Off)ST , Trick (T) , (0 - 10 v) V1 & Dali (D)

Emergency add EM to code (EM - Emergency)