

## SPIKE RANGE - GARDEN

### SPIKE LIGHT

## OUTDOOR

### SPIKE RANGE - GARDEN



CE SAA



bridgelux®

CREE

OSRAM

SAMSUNG

#### PRODUCT OVERVIEW

|                         |                                              |
|-------------------------|----------------------------------------------|
| Item Code               | 699246209928                                 |
| Code                    | SPK-A                                        |
| Product Name            | Spike Light ( Honey Comb )                   |
| Power                   | 5W                                           |
| Input Voltage           | DC24V                                        |
| Total Lumen Efficiency  | 400 lum                                      |
| LED CHIP BRAND          | Bridgelux/samsung/Cree/Osram                 |
| CRI                     | Ra≥90 / Ra≥95 (On request)                   |
| CCT                     | 1700K(Amber),2200K,2700K, 3000K ,4000K 6000K |
| Beam Angle              | 15°, 36°                                     |
| Lamp Cup                | Black / Corten                               |
| IP Rating               | IP67                                         |
| Driver Type             | EAGLERISE/MW/SWARVEN                         |
| Material                | Aluminum                                     |
| Dimention               | Spike                                        |
| Manufacturer's Warranty | 5 years                                      |
| Installation method     | Spike , 1M cable - GARDEN                    |

Swarven web : <https://swarven.com/>

Lumen efficiency can be increased upon request and based on the required quantity.

For coding pearpose

- 1-CCT :- For 2700K add W to code, For 3000k add L to code, For 4000K add D to code, for 6500K add S to code & For Tunable(2700K-6500K) add Z to code
- 2- Voltage : Put the number of the voltage ( 7 or 12 )
- 3- Beam angle : Put the number of the Angle ( 24° or 38° )
- 4- Put I with No. that need IP ( 20°40°&44° ) ( Ex : CR- Code , 7- W ,2700K - K, 24°- Beam Angle , IP20 - IP rating , D - Dali )
- 5- Driver : ( Triac, Leading Edg,0-10v,1-10v,zigbee & dally on required ) ( On / Off ) ST , Trick ( T ) , ( 0 - 10 v ) V , ( 1 - 10 v ) V1 & Dali ( D )
- 6- Emergency add EM to code ( EM - Emergency)