

UP RANGE - UP LIGHT

UP DIRECT

OUTDOOR

UP RANGE - DIRECT



bridgelux®

CREE

OSRAM

SAMSUNG



PRODUCT OVERVIEW

Item Code	699246209997
Code	UP-2
Product Name	Angle Range (Honey Comb)
Power	3W
Input Voltage	DC24V
Total Lumen Efficiency	280 lum
LED CHIP BRAND	Bridgelux/samsung/Cree/Osram
CRI	Ra≥90 / Ra≥95 (On request)
CCT	2700K/3000K/4000K/6500K
Beam Angle	10°, 15°, 25°, 40°, 60°
Lamp Cup	Red, blue,green, amber
IP Rating	IP67 Waterproof
Driver Type	EAGLERISE/MW/SWARVEN
Material	Aluminum / Heat Sink
Dimention	Ø54x93(mm)Diameter x length
Manufacturer's Warranty	5 years
Installation method	Inground uplight

Swarven web : <https://swarven.com/>

Lumen efficiency can be increased upon request and based on the required quantity.

For coding pearpose ,

1-CCT :- For 2700K add W to code, For 3000K add L to code, For 4000K add D to code, for 6500K add S to code & For Tunable(2700K-6500K) add Z to code

2- Voltage : Put the number of the voltage (7 or 12)

3- Beam angle : Put the number of the Angle (24* or 38*)

4- Put I with No. that need IP (20*40*&44*) (Ex : CR- Code , 7- W , 2700K - K , 24*- Beam Angle , IP20 - IP rating , D - Dali)

5- Driver : (Triac, Leading Edg, 0-10v,1-10v,zigbee & dally on required) (On / Off)ST , Trick (T) , (0 - 10 v) V , (1 - 10 v) V1 & Dali (D)

6- Emergency add EM to code (EM - Emergency)